

## DELAY LINES

ANOISON offers high performance delay line made from semi-rigid cable in confined space. If you provide such information as the delay time, space constraint, operating frequency, power and attenuation, we can offer custom delay line to meet your requirements.



Delay time [ns]	Length [m]	ANO SR086		ANO SR141		ANO SR250		ANO SR086AL		ANO SR141AL		ANO SR250AL	
		Weight [g]	Atten [dB]	Weight [g]	Atten [dB]	Weight [g]	Atten [dB]	Weight [g]	Atten [dB]	Weight [g]	Atten [dB]	Weight [g]	Atten [dB]
4.76	1.00	22.8	0.64	51.2	0.38	156.0	0.23	9.4	0.64	24.0	0.38	74.0	0.23
5.00	1.05	23.9	0.67	53.8	0.40	163.8	0.24	9.9	0.67	25.2	0.40	77.7	0.24
7.00	1.47	33.5	0.94	75.3	0.56	229.3	0.34	13.8	0.94	35.3	0.56	108.8	0.34
10.00	2.10	47.9	1.34	107.5	0.80	327.6	0.48	19.7	1.34	50.4	0.80	155.4	0.48
15.00	3.15	71.8	2.02	161.3	1.20	491.4	0.72	29.6	2.02	75.6	1.20	233.1	0.72
20.00	4.20	95.8	2.69	215.0	1.60	655.2	0.97	39.5	2.69	100.8	1.60	310.8	0.97

\*Max. attenuation at 1GHz

Delay line of semi-rigid cable does not have standard shape.